



To order, please ask for PTIDEX + Component (A/B) + Size + Bore + Rubber.

Also available in aluminium (BS2024) and steel (C45) on request.

Size	Component	Rubber part, rated torque (Nm)		Std bore (d)	Finished bore		Dimensions (mm)										Set screw	
		Yellow - Shore A 92	Red - Shore A 98		min	max	L	C	E	N	S	D	dh	Ba / Bd	G	M	t	
19/24	A	10	17	6	6-16	66	25	16	12	2,0	40	18	32	20	M5	10		
	B			6	6-24								40	-				
24/32	A	35	60	9	9-24	78	30	18	14	2,0	55	27	40	24	M5	10		
	B			9	9-32								55	-				
28/38	A	95	160	10	10-28	90	35	20	15	2,5	65	30	48	28	M8	15		
	B			10	10-38								65	-				
38/45	A	190	325	12	12-38	114	45	24	18	3,0	80	38	66	37	M8	15		
	B			12	12-45								78	37				
42/55	A	265	450	12	12-42	126	50	26	20	3,0	95	46	75	40	M8	20		
	B			12	12-55								94	40				
48/60	A	310	525	12	12-48	140	56	28	21	3,5	105	51	85	45	M8	20		
	B			12	12-60								104	45				
55/70	A	410	685	15	15-55	160	65	30	22	4,0	120	60	98	52	M10	20		
	B			15	15-70								118	52				
65/75	A	625	940	15	15-65	185	75	35	26	4,5	135	68	115	61	M10	20		
	B			15	15-75								133	61				
75/90	A	1280	1920	15	15-75	210	85	40	30	5,0	160	80	135	69	M10	25		
	B			15	15-90								158	69				
90/100	A	2400	3600	38	38-90	245	100	45	34	5,5	200	100	160	81	M12	25		
	B			38	38-100								180	81				